SAFETY DATA SHEET

Version 3.13 Revision Date 06/04/2015 Print Date 05/01/2016

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Acetone

Product Number : 90872

Brand : Sigma-Aldrich Index-No. : 606-001-00-8

CAS-No. : 67-64-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich

3050 Spruce Street SAINT LOUIS MO 63103

USA

Telephone : +1 800-325-5832 Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Sigma-Aldrich - 90872 Page 1 of 10

P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for P304 + P340 + P312 breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove P305 + P351 + P338 contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to P370 + P378 extinguish. P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 **Substances**

Formula C_3H_6O Molecular weight 58.08 g/mol CAS-No. 67-64-1 EC-No. 200-662-2 Index-No. 606-001-00-8

01-2119471330-49-XXXX Registration number

Hazardous components

Component	Classification	Concentration
Acetone		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

Sigma-Aldrich - 90872 Page 2 of 10

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

	n nonkpiace eei			
Component	CAS-No.	Value	Control parameters	Basis
			parameters	
Acetone	67-64-1	TWA	500.000000	USA. ACGIH Threshold Limit Values
			ppm	(TLV)
	Remarks	Central Nervous System impairment Hematologic effects		
		Upper Respiratory Tract irritation		tion
		Eye irritation		
		Adopted values or notations enclosed are those for which change		enclosed are those for which changes
		•	sed in the NIC	C

Sigma-Aldrich - 90872 Page 3 of 10

			es (NIC) a Biological Exposure Index or Indices
	Not classifiable as a human carcinogen		
	TWA	500 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Central Nervous System impairment		
	Hematologic effects		
	Upper Respiratory Tract irritation		
	Eye irritation Adopted values or notations enclosed are those for which changes		
	are proposed in the NIC		
	See Notice of Intended Changes (NIC)		
	Substances for which there is a Biological Exposure Index or Indices		
	(see BEI® section)		
	Not classifiable as a human carcinogen STEL 750.000000 USA. ACGIH Threshold Limit Values		
	SILL	ppm	(TLV)
	Central Nervous System impairment		
	Hematologic effects		
		ratory Tract irritation	on
	Eye irritation		
	Adopted values or notations enclosed are those for which changes		
	are proposed in the NIC See Notice of Intended Changes (NIC) Substances for which there is a Biological Exposure Index or Indices		
	(see BEI® section)		
	Not classifiable as a human carcinogen		
	STEL	750 ppm	USA. ACGIH Threshold Limit Values (TLV)
		ous System impair	rment
	Hematologic	: епестѕ ratory Tract irritatio	
	Eye irritation		111
	Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC)		
			a Biological Exposure Index or Indices
	(see BEI® section) Not classifiable as a human carcinogen		
	TWA	1,000.000000	USA. Occupational Exposure Limits
		ppm	(OSHA) - Table Z-1 Limits for Air
		2,400.000000	Contaminants
	The velve !-	mg/m3	L moto
	TWA	mg/m3 is approxir 250.000000	nate. USA. NIOSH Recommended
	1004	ppm	Exposure Limits
		590.000000	Exposure Enrite
		mg/m3	

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Acetone	67-64-1	Acetone	50.0000 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As	s soon as po	ssible after exposure	ceases)

Sigma-Aldrich - 90872 Page 4 of 10

Derived No Effect Level (DNEL)

Delived No Ellect Level (DNEL)					
Application Area	Exposure	Health effect	Value		
	routes				
Workers	Skin contact	Long-term systemic effects	186mg/kg BW/d		
Consumers	Ingestion	Long-term systemic effects	62mg/kg BW/d		
Consumers	Skin contact	Long-term systemic effects	62mg/kg BW/d		
Workers	Inhalation	Acute systemic effects	2420 mg/m3		
Workers	Inhalation	Long-term systemic effects	1210 mg/m3		
Consumers	Inhalation	Long-term systemic effects	200 mg/m3		

Predicted No Effect Concentration (PNEC)

	<u> </u>
Compartment	Value
Soil	33.3 mg/kg
Marine water	1.06 mg/l
Fresh water	10.6 mg/l
Marine sediment	3.04 mg/kg
Fresh water sediment	30.4 mg/kg
Onsite sewage treatment plant	100 mg/l

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators

Sigma-Aldrich - 90872 Page 5 of 10

and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Form: liquid, clear Appearance

Colour: colourless

b) Odour No data available

Odour Threshold No data available c)

рΗ No data available

Melting point/freezing

point

Melting point/range: -94 °C (-137 °F) - lit.

Initial boiling point and

boiling range

56 °C (133 °F) at 1,013 hPa (760 mmHg) - lit.

Flash point -16.99 °C (1.42 °F) - closed cup

Evaporation rate No data available h)

Flammability (solid, gas) No data available i)

Upper explosion limit: 13 %(V) Upper/lower flammability or Lower explosion limit: 2 %(V) explosive limits

Vapour pressure 533.3 hPa (400.0 mmHg) at 39.5 °C (103.1 °F)

245.3 hPa (184.0 mmHg) at 20.0 °C (68.0 °F)

Vapour density No data available

m) Relative density 0.791 g/cm3 at 25 °C (77 °F)

Water solubility completely miscible

Partition coefficient: noctanol/water

log Pow: -0.24

Auto-ignition 465.0 °C (869.0 °F)

temperature

Decomposition temperature

No data available

Viscosity No data available r) No data available Explosive properties Oxidizing properties No data available

9.2 Other safety information

> Surface tension 23.2 mN/m at 20.0 °C (68.0 °F)

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions 10.3

Vapours may form explosive mixture with air.

Sigma-Aldrich - 90872 Page 6 of 10

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Bases, Oxidizing agents, Reducing agents, Acetone reacts violently with phosphorous oxychloride.

10.6 Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5.800 mg/kg

Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Tremor. Behavioral:Headache. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

LC50 Inhalation - Rat - 8 h - 50,100 mg/m3

Remarks: Drowsiness Dizziness Unconsciousness

LD50 Dermal - Guinea pig - 7,426 mg/kg

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation

Eves - Rabbit

Result: Eye irritation - 24 h

Respiratory or skin sensitisation

- Guinea pig

Result: Does not cause skin sensitisation.

Germ cell mutagenicity

No data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Sigma-Aldrich - 90872 Page 7 of 10

Additional Information

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence Skin - Dermatitis - Based on Human Evidence Kidney - Irregularities - Based on Human Evidence Skin - Dermatitis - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

LC50 - Oncorhynchus mykiss (rainbow trout) - 5.540 mg/l - 96 h Toxicity to fish

Toxicity to daphnia and

other aquatic

LC50 - Daphnia magna (Water flea) - 8,800 mg/l - 48 h

invertebrates

Toxicity to algae Remarks: No data available

12.2 Persistence and degradability

Biodegradability Result: 91 % - Readily biodegradable

(OECD Test Guideline 301B)

12.3 **Bioaccumulative potential**

Does not bioaccumulate.

12.4 Mobility in soil

No data available

Results of PBT and vPvB assessment 12.5

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Packing group: II

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1090 Class: 3

Proper shipping name: Acetone Reportable Quantity (RQ): 5000 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 1090 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ACETONE

IATA

UN number: 1090 Class: 3 Packing group: II

Proper shipping name: Acetone

Sigma-Aldrich - 90872 Page 8 of 10

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Acetone	67-64-1	2007-03-01

Pennsylvania Right To Know Components

CAS-No. Revision Date 67-64-1 2007-03-01

New Jersey Right To Know Components

Acetone CAS-No. Revision Date 67-64-1 2007-03-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit. Eye irritation Flam. Lig. Flammable liquids

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical Hazard 0

NFPA Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0
Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

Further information

Copyright 2015 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Sigma-Aldrich - 90872 Page 9 of 10

Preparation Information Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Revision Date: 06/04/2015 Print Date: 05/01/2016 Version: 3.13

Sigma-Aldrich - 90872 Page 10 of 10