

# Part of Thermo Fisher Scientific

# SAFETY DATA SHEET

Creation Date 15-Apr-2009 Revision Date 27-Oct-2014 Revision Number 1

1. Identification

Product Name Ethyl ether

Cat No.: E138-1; E138-20; E138-4; E138-4LC; E138-500; E138RS-19;

E138RS-28; E138RS-50

Synonyms Ethyl ether; Ether

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Emergency Telephone Number

Fisher Scientific CHEMTREC®, Inside the USA: 800-424-9300
One Reagent Lane CHEMTREC®, Outside the USA: 001-703-527-3887
Fair Lawn, NJ 07410

Tel: (201) 796-7100

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids
Category 1
Acute oral toxicity
Category 4
Specific target organ toxicity (single exposure)
Category 3
Target Organs - Respiratory system, Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure)

Category 2

Specific target organ toxicity - (repeated exposure) Target Organs - Liver.

Aspiration Toxicity Category 1

Label Elements

### Signal Word

Danger

### **Hazard Statements**

Extremely flammable liquid and vapor
Harmful if swallowed
May cause respiratory irritation
May cause drowsiness or dizziness
May be harmful if swallowed and enters airways
May cause damage to organs through prolonged or repeated exposure



# **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

### Response

Get medical attention/advice if you feel unwell

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

# Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

# **Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

May form explosive peroxides

Repeated exposure may cause skin dryness or cracking

# 3. Composition / information on ingredients

Component	CAS-No	Weight %
Ethyl ether	60-29-7	>95

# 4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a

respiratory medical device. Obtain medical attention.

Revision Date 27-Oct-2014 Ethyl ether

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like Most important symptoms/effects

headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically Notes to Physician

# 5. Fire-fighting measures

**Suitable Extinguishing Media** CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire

with water spray.

**Unsuitable Extinguishing Media** Water may be ineffective

-45 °C / -49 °F **Flash Point** Method -No information available

**Autoignition Temperature** 

**Explosion Limits** 

160 °C / 320 °F

Upper 36.0 vol % Lower 1.9 vol %

Sensitivity to Mechanical Impact No information available **Sensitivity to Static Discharge** No information available

# Specific Hazards Arising from the Chemical

Extremely flammable. Risk of ignition. Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Containers may explode when heated. May form explosive peroxides. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Carbon monoxide (CO) Carbon dioxide (CO<sub>2</sub>) peroxides

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
1	4	1	N/A

### 6. Accidental release measures

**Personal Precautions** 

Use personal protective equipment, Remove all sources of ignition, Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Should not be released into the environment. See Section 12 for additional ecological information.

**Environmental Precautions** 

Up

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

# 7. Handling and storage

Handling

Wear personal protective equipment. Handle under an inert atmosphere. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Keep away from open flames, hot surfaces and sources of ignition. If peroxide formation is suspected, do not open or move container. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

**Storage** 

Flammables area. Store under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. May form explosive peroxides. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in

a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

# 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl ether	TWA: 400 ppm	(Vacated) TWA: 400 ppm	IDLH: 1900 ppm
	STEL: 500 ppm	(Vacated) TWA: 1200 mg/m <sup>3</sup>	
		(Vacated) STEL: 500 ppm	
		(Vacated) STEL: 1500 mg/m <sup>3</sup>	
		TWA: 400 ppm	
		TWA: 1200 mg/m <sup>3</sup>	

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Ethyl ether	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm
	TWA: 1210 mg/m <sup>3</sup>	TWA: 1200 mg/m <sup>3</sup>	STEL: 500 ppm
	STEL: 500 ppm	STEL: 500 ppm	
	STEL: 1520 mg/m <sup>3</sup>	STEL: 1500 mg/m <sup>3</sup>	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting/equipment.

**Personal Protective Equipment** 

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdoraromatic

Odor Threshold<br/>pHNo information available<br/>No information available

 Melting Point/Range
 -116 °C / -176.8 °F

 Boiling Point/Range
 34.6 °C / 94.3 °F

 Flash Point
 -45 °C / -49 °F

Evaporation Rate 37.5

Flammability (solid,gas) Not applicable

Flammability or explosive limits

**Upper** 36.0 vol % **Lower** 1.9 vol %

Vapor Pressure 587 mbar @ 20 °C

Vapor Density2.55Relative Density0.714

SolubilitySlightly soluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature160 °C / 320 °FDecomposition TemperatureNo information availableViscosity0.2448 cP at 20 °C

Molecular Formula C4 H10 O Molecular Weight 74.12

# 10. Stability and reactivity

Reactive Hazard Yes

Stability May form explosive peroxides. Air sensitive. Light sensitive. Hygroscopic.

Conditions to Avoid Incompatible products. Heat, flames and sparks. Exposure to air. Exposure to light.

Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** May form explosive peroxides.

# 11. Toxicological information

## **Acute Toxicity**

### **Product Information**

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	Not listed	

**Toxicologically Synergistic** 

**Products** 

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

 Irritation
 No information available

 Sensitization
 No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ī	Ethyl ether	60-29-7	Not listed				

Mutagenic Effects Mutagenic effects have occurred in experimental animals.

Reproductive Effects

No information available.

Developmental Effects

No information available.

**Teratogenicity** No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure Liver

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting

**Endocrine Disruptor Information** 

No information available

**Other Adverse Effects** 

See actual entry in RTECS for complete information.

# 12. Ecological information

#### **Ecotoxicity**

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	10000 mg/L LC50 96 h 2560	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h
		mg/L LC50 96 h		_

Persistence and Degradability Bioaccumulation/ Accumulation

Persistence is unlikely based on information available.

No information available.

Mobility

Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl ether	0.82

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes		
Ethyl ether - 60-29-7	U117	=		

# 14. Transport information

DOT

UN-No UN1155
Proper Shipping Name UN1155
Diethyl ether

Hazard Class 3
Packing Group I

**TDG** 

UN-No UN1155
Proper Shipping Name Diethyl ether

Hazard Class 3 Packing Group 1

IATA

UN-No UN1155
Proper Shipping Name Diethyl ether

Hazard Class 3 Packing Group 1

IMDG/IMO

UN-No UN1155
Proper Shipping Name Diethyl ether

Hazard Class 3
Packing Group

# 15. Regulatory information

## **International Inventories**

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethyl ether	Х	Х	-	200-467-2	-		Х	Х	Χ	Х	Х

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

Revision Date 27-Oct-2014

- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

#### U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

# SARA 311/312 Hazardous Categorization

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard Yes

Clean Water Act Not applicable

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

Not applicable

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethyl ether	100 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals

#### State Right-to-Know

	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island	
I	Ethyl ether	X	X	X	=	Х	

### **U.S.** Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

#### U.S. Department of Homeland Security

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard
Ethyl ether	7500 lb STQ

#### Other International Regulations

Mexico - Grade Severe risk, Grade 4

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and

## the MSDS contains all the information required by the CPR

WHMIS Hazard Class B2 Flammable liquid

D1B Toxic materials D2B Toxic materials



## 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 15-Apr-2009

 Revision Date
 27-Oct-2014

 Print Date
 27-Oct-2014

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

#### **Disclaimer**

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**